
Datasheet

Connection Module Cat. 6, 1xRJ45/u, Snap-in, 10x

R810598

24 pcs



- RJ45 Cat. 6 connection module, unshielded
- Snap-in adapter
- Dust cover
- Cable tie
- Installation instructions

090.7078

FEATURE

- As part of a Cat. 6 channel, the connection module exceeds the minimum requirements of the IEEE 802.3™ Section Four standard on 10GBASE-T performance, as well as the requirements for Class E_A performance acc. to ISO/IEC 11801 and Cat. 6_A performance according to TIA 568.2-D
- Exceeds Cat.6 specifications acc. to ISO/IEC 11801, EN 50173 and TIA 568.2-D in the entire admissible range
- Maximum reliability through special contact design without internal transfer points
- Capacitive and inductive compensation
- 3P and UL certified

TECHNICAL DATA

DESCRIPTION	VALUE/VALUE RANGE
Standard / norm	EN 50173-1 IEC 60603-7: Electrical Characteristics of the Telecommunication Outlets ISO/IEC 11801
Protection class IP	IP 10 (correlates to NEMA 1)
Connector class	connection module
Shielding connector (A)	unshielded
Connector type (A)	RJ45
Category connector (A)	Cat. 6
Holder for connector / module	Snap-in
Wiring diagram	T568A and T568B
Poles	8

MECHANICAL DATA

DESCRIPTION	VALUE/VALUE RANGE
Dimensions	18.2 mm x 22.7 mm x 41.3 mm / 0.717 in x 0.894 in x 1.626 in (W x H x D)
Color	green

Reichle & De-Massari AG. Subject to technical changes and misprintswww.rdm.com - ©2019

Connection Module Cat. 6, 1xRJ45/u, Snap-in, 10x

R810598

24 pcs

DESCRIPTION	VALUE/VALUE RANGE
Material	plastic: PC, UL 94 V-0

Reichle & De-Massari AG. Subject to technical changes and misprintswww.rdm.com - ©2019